

PL-6KDT



Parking Lifts

SKU# 5175157

12,000-lb. Cap. Parking Lift / Tandem / Independent Platforms

Questions? Contact BendPak's Sales Team

sales@bendpak.com | 1-800-253-2363

Monday - Friday, 6AM to 4:30PM PST

Safely Converts Your Two-Car Garage into a Four-Car Garage

The PL-6KDT is an indoor-outdoor tandem-style [parking lift](#) that holds a total of four vehicles in its 224" x 205" x 103" frame. Dual hydraulic cylinders and a pair of stabilizing lifting cables support two lifting platforms. The cables are routed internally throughout the parking lift.

This lift is intended for use by anyone with four vehicles and a wide garage area to store them. You'll be surprised to see how well this unit fits in a variety of garage sizes. In the right space, it can be successfully utilized for commercial or residential purposes.

Features

- 6,000-lb. capacity per deck
- Perfect for cars, light trucks, motorcycles and ATVs
- Rugged I-beam and C-channel construction
- Built-in wheel stops
- Wide base-plate for maximum stability
- Front and rear wheel chocks
- Superstructure features durable powder-coat finish
- Dual hydraulic cylinders with heavy-duty steel lifting cable
- Heavy-duty steel construction
- Reliable electric-hydraulic power system
- Full-width platform to keep bottom vehicles protected
- Simple controls
- Oversized sheave diameter reduces cable fatigue
- High-speed lifting
- Features heavy-duty 3/8" aircraft cable
- Rugged 1.25" roller axles
- Multi-position safety locks in each column
- Runways feature non-skid surface
- Push-button pneumatic safety release
- Independent backup slack-cable safety latches
- Customizable power unit location



Specifications

Lifting Capacity	6,000 lbs. (2,722 kg)
Overall Width	211" (5,352 mm)
Overall Length	236.5" (6,008 mm)
Overall Height	123.75" (3,140 mm)
Min. Runway Height	9" (230 mm)
Max. Rise	89" (2,261 mm)
Width Between Posts	185.5" (4,715 mm)
Platform Width	82" (2,086 mm)
Platform Length	152" (3,862 mm)
Drive-thru Clearance	93" (2,374 mm)
Locking Positions	1 / Adjustable
Lifting Time	30 sec
Standard Motor	220 VAC / 60 Hz / 1Ph

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2011 or ANSI/UL 201. Consult www.autolift.org for complete listings or contact BendPak via contact@bendpak.com.